

INDUSTRIAL COMPONENT DATA

HC-26S1N122300X 1240143 PHOENIX CONTACT Conect. plug. to be apar. front wall, straight, Screw lock, M27, num..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-26S1N122300X



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-26S1N122300X
Catalog number	1240143
Category	Circular connector, mounting (without cable)
Minimum order	24 Pcs
Document ID	EO-B0E9A3AB9A
Generated	2026-08-06

Product Overview

Conect. plug. to be apar. front wall, straight, Screw lock, M27, number of poles: 26, contact connection type: Female, Flat joint, shielded: yes, number of poles: 26, connection type: Solder cup, series: HC, The item does not contain lead according to the RoHS II directive without exception 6c (Pb< 0.1%)

Connect. plug in. to apar. wall delant.

Device connector front mounting, straight, Screw locking mechanism, M27, number of positions: 26, contact connection type: Socket, Flat gasket, 4x Ø 3.2, shielded: yes, degree of protection: IP67, number of positions: 26, connection method: Solder connection, series: HC, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT
--------------	-----------------

Additional Product Information

Technical dataMountingMounting 4x Ø 3.2

Connection method Solder connection

Product propertiesProduct type Circular connectors (device side)

Number of positions 26

Connection profile 26

Application Signal

Series HC

Shielded yes

Coding N

Thread type M27
Material specifications Flammability rating according to UL 94 V0
Seal material FPM or NBR or EPDM
Housing material Metal
Electrical properties Contact
Contact diameter 1 mm
Min. cross section 0.08 mm²
Max. cross section 1 mm²
Max. current 8 A
Nominal voltage UN 48 V AC 74 V DC
Overvoltage category III
Degree of pollution 3
Rated surge voltage 1.5 kV
Connection data Conductor connection
Connection method Solder connection
Contact connection type Socket
Mechanical properties Mechanical data
Insertion/withdrawal cycles 50
Connector Type straight
Direction of rotation Standard
Environmental and real-life conditions Ambient conditions
Degree of protection IP67
Ambient temperature (operation) -20 °C ... 125 °C
Altitude 2000 m

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-26S1N122300X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.