

INDUSTRIAL COMPONENT DATA

HC-A10-I-PT-M 1585359 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-A10-I-PT-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-A10-I-PT-M
Catalog number	1585359
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-9AC0BF3813
Generated	2026-08-05

Product Overview

Contact insert

Contact insert, number of poles: 10+PE, size: D15, number of connections per pole: 1, Male, Push-in connection, 250 V, 16 A, 0.14 mm² ... 2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1585359

Packing unit 1 pc

Catalog page Page 513 (C-2-2017)

GTIN 4046356285087

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 85366990

Country of origin CN (China)

General

Note For HEAVYCON housing of type D15

Connectors may be operated only when there is no load/voltage.

For solid conductors or stranded conductors with ferrules

Connection method Push-in connection

Screwdriver blade 0.5 x 3.5 mm

Number of connections per position 1
Degree of pollution 3
Overvoltage category III
Number of positions 10+PE
Insertion/withdrawal cycles ≥ 500
Size D15
Contact numbering 1 - 10
Conductor cross section 0.14 mm² ... 2.5 mm² (applies to stranded conductors with ferrules)
Connection cross section AWG 26 ... 14
Stripping length of the individual wire 8 mm
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Connection
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)
Material data
Contact material Copper alloy
Contact surface material Ag
Contact carrier material PC
Electrical characteristics
Rated voltage (III/3) 250 V
Rated surge voltage 4 kV
4 kV
Rated current 16 A
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classification...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-A10-I-PT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.