

INDUSTRIAL COMPONENT DATA

HC-ADV-B06-HLWH-1TTM25-MF-BK 1420905 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-ADV-B06-HLWH-1TTM25-MF-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-ADV-B06-HLWH-1TTM25-MF-BK
Catalog number	1420905
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-183F97D18F
Generated	2026-08-05

Product Overview

Housing

B6 aerial housing, with screw lock, material: Die-cast aluminium, seawater resistant, cable outlets: 1, straight, 1x M25, height: 74 mm, cable gland: without, increased environmental requirements

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Technical dataNotesGeneral For contact inserts HC-B6, BB10, DD24, M

Product propertiesProduct type Housing with screw locking

Housing type Sleeve housing

Product family HC-ADV

Application increased environmental requirements

Type B6

No. of cable outlets 1

Type of the screw connection 1x M25

Type Low design

Fixing screws M6 (screw head: 5 mm Allen screw)

Shielded no

Cable outlet straight

Pg screw connection none

Data management status

Article revision 01

Connection data Tightening torque 3 Nm ... 5 Nm (for M6 mounting screws on the sleeve housing)

Dimensions Dimensional drawing

Width 57 mm

Height 74 mm

Length 92 mm

Installation dimensions

Width of the assembly cutout 35 mm

Length of the assembly cutout 52 mm

Material specifications Seal material Viton

Housing material Die-cast aluminum, salt water resistant

Housing surface material Powder-coated, black

Locking latch material Stainless steel

Environmental and real-life conditions Ambient conditions

Degree of protection IP66

IP68 (0.2 bar/24 h)

IP69 (ISO 20653:2013-02)

Enclosure rating (NEMA) 4 (UL 50e)

4X (UL 50e)

12 (UL 50e)

Impact strength IK09

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical properties Mechanical data

Type of the screw connection 1x M25

Locking type Screw

Mounting Fixing screws M6 (screw head: 5 mm Allen screw)

ETIM for 1420905 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

57 mm

Height (EF000040)

74 mm

Depth (EF000049)

92 mm

Type of housing (EF006980)

Plug case

Housing material (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-ADV-B06-HLWH-1TTM25-MF-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.