

INDUSTRIAL COMPONENT DATA

HC-ADV-B24-1TM32-1SM25-EMC-PS 1423228 PHOENIX CONTACT Housing HC-ADV-B24-1TM32-1SM25-EMC-PS 1423228

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-ADV-B24-1TM32-1SM25-EMC-PS



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-ADV-B24-1TM32-1SM25-EMC-PS
Catalog number	1423228
Category	Housing for rectangular connectors
Minimum order	50 Pcs
Document ID	EO-747FF45510
Generated	2026-08-06

Product Overview

Housing - HC-ADV-B24-1TM32-1SM25-EMC-PS - 1423228

B24 Aerial Housing, Screw Lock, Material: Die-cast Aluminum, Seawater Resistant, Cable Outlets: 2, Straight, Side, Height: 93.7 mm, Cable Gland: Without, Tubing: No, 1x M32 / 1x M25, Offshore/EMC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Sleeve housing B24, Screw locking, material: Die-cast aluminum, salt water resistant, cable outlets: 2, straight, lateral, height: 93.7 mm, cable gland: none, support sleeve: no, 1x M32 / 1x M25, Offshore/EMC

Key Commercial Data

Orderkey 1423228

Packing unit 1

GTIN 4055626327907

Custom tariff number 85389099

Dimensions

Height 93.7 mm

Width 57 mm

Length 152 mm

Length of the assembly cutout 112 mm

Width of the assembly cutout 35 mm

Ambient conditions

Degree of protection of housing (IP) IP66

IP68 (0.2 bar/24 h)

Degree of protection of housing (NEMA) 4 (NEMA 250)

4X (NEMA 250)

6P (NEMA 250)

12 (NEMA 250)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M

Size B24

Housing type Sleeve housing

Locking type Screw locking

Torque 3 Nm (Locking screw)

Fixing screws M6 (screw head: Pozidrive)

No. of cable outlets 2

Cable outlet straight, lateral

Screw connection none

Type of the screw connection 1x M32 / 1x M25

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

Seal material NBR, conductive

Material of locking screw Stainless steel

Assembly instructions M6 locking screw, with Pozidrive head

Connection To ensure optimum shielding, any insulating power coating must be removed from the profile gasket area on the control cabinet panel. Tightening torque of locking screw: 3 Nm.

Classifications

eCl@ss

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 9.0 27440202

ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-ADV-B24-1TM32-1SM25-EMC-PS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.