

INDUSTRIAL COMPONENT DATA

HC-B 16-AML-EVO 1412276 PHOENIX CONTACT HEAVYCON B16 panel mounting base with single locking latch, height: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-AML-EVO



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-AML-EVO
Catalog number	1412276
Category	Housing for rectangular connectors
Minimum order	50 Pcs
Document ID	EO-07B383B28B
Generated	2026-08-01

Product Overview

HEAVYCON B16 panel mounting base with single locking latch, height: 29 mm, with flat gasket, with EVO plastic latch
Recessed housing HEAVYCON B16 with longitudinal flange, height 29 mm, with flat joint, with EVO plastic flange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1412276

Packing unit 1

GTIN 4046356952453

Custom tariff number 85389099

Drawings

Ambient conditions

Environmental Product Compliance

Dimensions

General

Classifications

Drawings

Dimensional drawing

Dimensional drawing

[Dimensional drawing](#)

[Mounting cutout](#)

[Back to top](#)[Dimensions](#)

Height 29 mm

Width 43 mm

Length 114 mm

Length of the assembly cutout 86 mm

Width of the assembly cutout 35 mm

[Back to top](#)[Ambient conditions](#)

Degree of protection of housing (IP) IP65 (When plugged in)

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)[General](#)

Note For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K

Size B16

Housing type Panel mounting base

Locking type with single locking latch

Torque 1.5 Nm ... 2 Nm (Mounting screw)

Screw connection none

Housing material Aluminum die-cast

Housing surface material Powder-coated, gray

Material lock Stainless steel, handle: PA

Material grip body interlock PA

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)[ETIM](#)

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)[UNSPSC](#)

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 31261501

UNSPSC 20.0 31261501

UNSPSC 21.0 31261501

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-AML-EVO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.