

INDUSTRIAL COMPONENT DATA

HC-B 16-KMQ-H-O1STM40 1414349 PHOENIX CONTACT HEAVYCON B16 coupling housing, with double locking latch, heig..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-KMQ-H-O1STM40



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-KMQ-H-O1STM40
Catalog number	1414349
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-09D08F9882
Generated	2026-08-03

Product Overview

HEAVYCON B16 coupling housing, with double locking latch, height: 82 mm, with 1 x M40 thread, straight cable outlet
HEAVYCON B16 coupling box, with cross flange, height 82 mm, with 1x M40 thread, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1414349

Packing unit 1 pc

Minimum order quantity 10 pc

GTIN 4055626023885

Weight per Piece (excluding packing) 240.000 g

Custom tariff number 85389099

Country of origin DE (Germany)

Drawings

Ambient conditions

Environmental Product Compliance

Dimensions

[General](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Dimensional drawing](#)

[Back to top](#)[Dimensions](#)

[Height 82 mm](#)

[Back to top](#)[Ambient conditions](#)

[Degree of protection IP65](#)

[Ambient temperature \(operation\) -40 °C ... 125 °C](#)

[Back to top](#)[General](#)

[Note](#) For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K

[Type B16](#)

[Degree of protection IP65](#)

[Locking type with double locking latch](#)

[Type of the screw connection 1x M40](#)

[Pg screw connection none](#)

[Cable outlet straight](#)

[Housing material Aluminum die-cast](#)

[Housing surface material Powder-coated, gray](#)

[Seal material NBR](#)

[Ambient temperature \(operation\) -40 °C ... 125 °C](#)

[Back to top](#)[Environmental Product Compliance](#)

[China RoHS](#) Environmentally friendly use period: unlimited = EFUP-e

[No hazardous substances above threshold values](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 10.0.1 27440202](#)

[eCl@ss 5.1 27261200](#)

[eCl@ss 6.0 27261200](#)

[eCl@ss 7.0 27440202](#)

[eCl@ss 8.0 27440202](#)

[eCl@ss 9.0 27440202](#)

[Back to top](#)[ETIM](#)

[ETIM 5.0 EC000437](#)

[ETIM 6.0 EC000437](#)

[ETIM 7.0 EC000437](#)

[Back to top](#)[UNSPSC](#)

[UNSPSC 13.2 31261501](#)

[UNSPSC 18.0 31261501](#)

[UNSPSC 19.0 31261501](#)

[UNSPSC 20.0 31261501](#)

[UNSPSC 21.0 31261501](#)

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-KMQ-H-O1STM40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.