

INDUSTRIAL COMPONENT DATA

HC-B 24-TFQ-N-O1PG21G 1460220 PHOENIX CONTACT HEAVYCON B24 sleeve housing, for double locking latch, height:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-TFQ-N-O1PG21G



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-TFQ-N-O1PG21G
Catalog number	1460220
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-2983EE5F34
Generated	2026-08-05

Product Overview

HEAVYCON B24 sleeve housing, for double locking latch, height: 65 mm, with 1 x Pg21 gland, straight cable outlet
HEAVYCON B24 aerial housing, for transverse lock, height 65 mm, with 1x Pg21 tubing, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1460220

Packing unit 1 pc

Minimum order quantity 10 pc

GTIN 4046356794244

Weight per Piece (excluding packing) 238.000 g

Custom tariff number 85389099

Country of origin DE (Germany)

Drawings

Ambient conditions

Environmental Product Compliance

Dimensions

[General](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Dimensional drawing](#)

[Back to top](#)[Dimensions](#)

Height 65 mm

Width 43 mm

Length 120 mm

[Back to top](#)[Ambient conditions](#)

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)[General](#)

Note For contact inserts HC-B24, BB46, BBB64, D64, DD108, M

Size B24

Housing type Sleeve housing

Locking type for double locking latch

No. of cable outlets 1

Cable outlet straight

Screw connection none

Type of the screw connection 1x Pg21

Housing material Aluminum die-cast

Housing surface material Powder-coated, gray

Assembly instructions For half and full screw connections

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140800

eCl@ss 4.1 27140800

eCl@ss 5.0 27143400

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)[ETIM](#)

ETIM 3.0 EC000437

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)[UNSPSC](#)

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502

UN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-TFQ-N-O1PG21G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.