

INDUSTRIAL COMPONENT DATA

HC-B 48-TFL-96/O1STM50S 1460351 PHOENIX CONTACT HEAVYCON sleeve housing B48, for single locking latch, heigh..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 48-TFL-96/O1STM50S



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 48-TFL-96/O1STM50S
Catalog number	1460351
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-C91BA1AB68
Generated	2026-08-04

Product Overview

HEAVYCON sleeve housing B48, for single locking latch, height 96 mm, with thread 1x M50, lateral conductor exit
HEAVYCON B48 aerial housing, for longitudinal flange, height of 96 mm, with 1 x M50 thread, side cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1460351

Packing unit 1 pc

Catalog page Page 635 (C-2-2017)

GTIN 4046356696579

Weight per Piece (excluding packing) 620.000 g

Custom tariff number 85389099

Country of origin DE (Germany)

Drawings

Ambient conditions

Environmental Product Compliance

Dimensions

[General](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Dimensional drawing](#)

[Back to top](#)[Dimensions](#)

Height 96 mm

Width 89 mm

Length 131.5 mm

[Back to top](#)[Ambient conditions](#)

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)[General](#)

Note For contact inserts HC-B48, DD216, M

Size B48

Housing type Sleeve housing

Color gray

Locking type for single locking latch

No. of cable outlets 1

Cable outlet lateral

Screw connection none

Type of the screw connection 1x M50

Housing material Aluminum die-cast

Housing surface material Powder-coated, gray

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140800

eCl@ss 4.1 27140800

eCl@ss 5.0 27143400

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)[ETIM](#)

ETIM 3.0 EC000437

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)[UNSPSC](#)

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502
UNSPSC 12.01 31261502
UNSPSC 13.2 31261501
UNSPSC 18.0 31261501...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 48-TFL-96/O1STM50S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.