

INDUSTRIAL COMPONENT DATA

HC-B24-I-TPT-F 1423022 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B24-I-TPT-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B24-I-TPT-F
Catalog number	1423022
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-994172A279
Generated	2026-08-01

Product Overview

Contact insert

Contact insert, number of poles: 24+PE, size: B24, number of connections per pole: 2, Female, Push-in connection, 500 V, 16 A, 0.25 mm² ... 1.5 mm², Application: Power

Contact insert, number of positions: 24+PE, size: B24, number of connections per position: 2, Socket, Push-in connection, 500 V, 16 A, 0.25 mm² ... 1.5 mm², application: Power

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral Use only flexible conductors with ferrule (in conjunction with CRIMPFOX 6 only)

General Connectors may be operated only when there is no load/voltage.

MountingAssembly note To ensure correct use, installation in housing with IP54 protection or better is required

Product propertiesProduct type Contact insert with a fixed no. of positions

Series HC-B

Application Power

Type B24

B48

Number of positions 24

Connection profile 24+PE

Contact numbering 1 - 24

Number of connections per position 2

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

DimensionsDimensional drawing

Width 34 mm

Height 34.6 mm

Length 111 mm

Drill hole distance, horizontal 104 mm

Mechanical characteristics

Contact diameter 2.5 mm

Connection dataConnection technology

Connection technology Push-in connection

Number of connections per position 2

Conductor connection

Conductor cross section 0.25 mm² ... 1.5 mm²

Connection cross section AWG 24 ... 16

Tightening torque 0.8 Nm ... 1.2 Nm (PE connection)

0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)

Stripping length of the individual wire 8 mm ±1 mm

Electrical propertiesRated voltage (III/3) 500 V

Rated surge voltage 6 kV

Rated current 16 A

Mechanical propertiesMechanical data

Insertion/withdrawal cycles ≥ 500

Material specificationsFlammability rating according to UL 94 V0

Contact material Copper alloy

Contact surface material Ag

Contact carrier mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B24-I-TPT-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.