

INDUSTRIAL COMPONENT DATA

HC-BB10-I-PT-M 1014418 PHOENIX CONTACT Contact insert, number of positions: 10+PE, size: B6, power contacts:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-BB10-I-PT-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-BB10-I-PT-M
Catalog number	1014418
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-2B0D2A30D4
Generated	2026-08-06

Product Overview

Contact insert, number of positions: 10+PE, size: B6, power contacts: 10, control contacts: 0, number of connections per position: 1, Pin, Push-in connection, 500 V, 16 A, 0.5 mm² ... 2.5 mm², application: Power

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1014418

Packing unit 1 pc

Catalog page Page 553 (C-2-2019)

GTIN 4055626494418

Weight per Piece (excluding packing) 60.000 g

Custom tariff number 85366990

Country of origin CN (China)

Drawings

Ambient conditions

Electrical characteristics

Environmental Product Compliance

General

Material data

Standards and Regulations

Classifications

Drawings

Dimensional drawing

Mounting cutout when used without housing

[Back to top](#)General

Note Connectors may be operated only when there is no load/voltage.

Connection method Push-in connection

Number of connections per position 1

Degree of pollution 3

Overvoltage category III

Number of positions 10+PE

No. of power contacts 10

No. of control contacts 0

Insertion/withdrawal cycles ≥ 500

Size B6

Contact numbering 1 - 10

Conductor cross section 0.5 mm² ... 2.5 mm² (with ferrule)

Connection cross section AWG 20 ... 14 (with ferrule)

Stripping length of the individual wire 10 mm

Minimum housing height 72 mm

Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)

[Back to top](#)Material data

Contact material Copper alloy

Contact surface material Ag

Contact carrier material PC

[Back to top](#)Electrical characteristics

Rated voltage (III/3) 500 V

Rated surge voltage 6 kV

Rated current 16 A (power contacts)

[Back to top](#)Standards and Regulations

Flammability rating ac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-BB10-I-PT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.