

INDUSTRIAL COMPONENT DATA

HC-COM-BWS-EL-AL 1078594 PHOENIX CONTACT Panel mounting base COM, with single locking latch, material: Die-c..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-BWS-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-BWS-EL-AL
Catalog number	1078594
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-36B96B05D7
Generated	2026-07-31

Product Overview

Panel mounting base COM, with single locking latch, material: Die-cast aluminum, salt water resistant, height: 19.8 mm, cable gland: none, support sleeve: no, Standard

COM recessed housing, with longitudinal flange, material: Die-cast aluminium, seawater resistant, height: 19.8 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1078594

Packing unit 1 pc

Catalog page Page 653 (C-2-2019)

GTIN 4055626794129

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 76169990

Country of origin CN (China)

Drawings

Ambient conditions

[Standards and Regulations](#)

[Dimensions](#)

[General](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Dimensional drawing](#)

[Mounting cutout](#)

[Back to top](#)[Dimensions](#)

Height 19.8 mm

Width 39 mm

Length 45.8 mm

[Back to top](#)[Ambient conditions](#)

Degree of protection (IP) IP66

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)[General](#)

Size COM

Housing type Panel mounting base

Color gray aluminum

Locking type with single locking latch

Screw connection none

Housing material Die-cast aluminum, salt water resistant

Seal material NBR

Material lock PA

Flammability rating according to UL 94 V0

[Back to top](#)[Standards and Regulations](#)

Flammability rating according to UL 94 V0

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140816

eCl@ss 4.1 27140816

eCl@ss 5.0 27143424

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)[ETIM](#)

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)[UNSPSC](#)

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502

UNSPSC 12.01 31261502

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 31261501

UNSPSC 20.0 31261501

UNSPSC 21.0 31261501

Back to top

ETIM for 1078594 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-BWS-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.