

**INDUSTRIAL COMPONENT DATA**

# HC-COM-BWS-PL-BK 1012538 PHOENIX CONTACT Panel mounting base COM, with single locking latch, material: PA, h..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-BWS-PL-BK



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | PHOENIX CONTACT                    |
| MPN / Reference | HC-COM-BWS-PL-BK                   |
| Catalog number  | 1012538                            |
| Category        | Housing for rectangular connectors |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-77EE5EAA4D                      |
| Generated       | 2026-08-02                         |

## Product Overview

Panel mounting base COM, with single locking latch, material: PA, height: 18.5 mm, cable gland: none, support sleeve: no, Standard

COM recessed housing, with longitudinal flange, material: PC, height: 20 mm, cable gland: without, Standard

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

## Additional Product Information

**Key Commercial Data**

Orderkey 1012538

Packing unit 1 pc

Catalog page Page 652 (C-2-2019)

GTIN 4055626489193

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 85389099

Country of origin CN (China)

Drawings

Ambient conditions

Standards and Regulations

[Classifications](#)

[Dimensions](#)

[General](#)

[Environmental Product Compliance](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to top](#)[Dimensions](#)

Height 18.5 mm

Width 39 mm

Length 45.8 mm

[Back to top](#)[Ambient conditions](#)

Degree of protection (IP) IP66

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)[General](#)

Size COM

Housing type Panel mounting base

Color black

Locking type with single locking latch

Screw connection none

Housing material PA

Seal material NBR

Material lock PA

Flammability rating according to UL 94 V0

[Back to top](#)[Standards and Regulations](#)

Flammability rating according to UL 94 V0

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140816

eCl@ss 4.1 27140816

eCl@ss 5.0 27143424

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)[ETIM](#)

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)[UNSPSC](#)

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502  
UNSPSC 12.01 31261502  
UNSPSC 13.2 31261501  
UNSPSC 18.0 31261501  
UNSPS...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-BWS-PL-BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.