

INDUSTRIAL COMPONENT DATA

HC-COM-HHFS-1TTM25-EL-AL 1078590 PHOENIX CONTACT

Sleeve housing COM, for single locking latch, material: Die..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-HHFS-1TTM25-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-HHFS-1TTM25-EL-AL
Catalog number	1078590
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-2C21A925F1
Generated	2026-08-04

Product Overview

Sleeve housing COM, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, height: 68 mm, cable gland: none, support sleeve: no, 1x M25, Standard

COM aerial housing, for longitudinal flange, material: Die-cast aluminum, seawater resistant, cable outlets: 1, straight, 1x M25, height: 68 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1078590

Packing unit 1 pc

Catalog page Page 653 (C-2-2019)

GTIN 4055626791890

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85389099

Country of origin CN (China)

Drawings

Ambient conditions

Standards and Regulations

Dimensions

General

Classifications

Drawings

Dimensional drawing

Back to topDimensions

Height 68 mm

Width 39 mm

Length 48.8 mm

Back to topAmbient conditions

Degree of protection (IP) IP66

Ambient temperature (operation) -40 °C ... 125 °C

Back to topGeneral

Size COM

Housing type Sleeve housing

Color gray aluminum

Locking type for single locking latch

No. of cable outlets 1

Cable outlet straight

Screw connection none

Type of the screw connection 1x M25

Housing material Die-cast aluminum, salt water resistant

Flammability rating according to UL 94 V0

Back to topStandards and Regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140816

eCl@ss 4.1 27140816

eCl@ss 5.0 27143424

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

Back to topETIM

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

Back to topUNSPSC

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502

UNSPSC 12.01 31261502

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 31261501

UNSPSC 20.0 31261501

UNSPSC 21.0 31261501

Back to top

ETIM for 1078590 Connectors (EC000437)

Feature Name

Feature Value

Width (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-HHFS-1TTM25-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.