

INDUSTRIAL COMPONENT DATA

HC-COM-SHOWS-1SGM25-PL-BK 1079393 PHOENIX CONTACT Box mounting bases COM, with single locking latch, materia..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-SHOWS-1SGM25-PL-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-SHOWS-1SGM25-PL-BK
Catalog number	1079393
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-831FE81FE0
Generated	2026-08-02

Product Overview

Box mounting bases COM, with single locking latch, material: PA, cable outlets: 1, lateral, height: 68 mm, cable gland: with, support sleeve: no, 1x M25, Standard

COM socket housing, with longitudinal flange, material: PA, cable outlets: 1, side, 1x M25, height: 36 mm, cable gland: with, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1079393

Packing unit 1 pc

Catalog page Page 652 (C-2-2019)

GTIN 4055626798493

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85389099

Country of origin CN (China)

Drawings

Ambient conditions

Standards and Regulations

Classifications

Dimensions

General

Environmental Product Compliance

Drawings

Dimensional drawing

[Back to top](#)Dimensions

Height 68 mm

Wrench size, union nut 27 mm

External cable diameter 10 mm ... 16 mm

[Back to top](#)Ambient conditions

Degree of protection (IP) IP66

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)General

Size COM

Housing type Box mounting bases

Color black

Locking type with single locking latch

No. of cable outlets 1

Cable outlet lateral

Screw connection with

Type of the screw connection 1x M25

Housing material PA

Seal material NBR

Material lock PA

Flammability rating according to UL 94 V0

[Back to top](#)Standards and Regulations

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

REACH SVHC Lead 7439-92-1

[Back to top](#)Classifications

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140816

eCl@ss 4.1 27140816

eCl@ss 5.0 27143424

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)ETIM

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)UNSPSC

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502

UNSPSC 12.01 31261502

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-SHOWS-1SGM25-PL-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.