

INDUSTRIAL COMPONENT DATA

HC-COM-SHOWS-1SGM25-PL-BK 1079393 PHOENIX CONTACT Box mounting bases COM, with single locking latch, materia..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-SHOWS-1SGM25-PL-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-SHOWS-1SGM25-PL-BK
Catalog number	1079393
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-831FE81FE0
Generated	2026-08-04

Product Overview

Box mounting bases COM, with single locking latch, material: PA, cable outlets: 1, lateral, height: 68 mm, cable gland: with, support sleeve: no, 1x M25, Standard

COM socket housing, with longitudinal flange, material: PA, cable outlets: 1, side, 1x M25, height: 36 mm, cable gland: with, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1079393

Packing unit 1 pc

Catalog page Page 652 (C-2-2019)

GTIN 4055626798493

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85389099

Country of origin CN (China)

Drawings

Ambient conditions

[Standards and Regulations](#)

[Classifications](#)

[Dimensions](#)

[General](#)

[Environmental Product Compliance](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to top](#)[Dimensions](#)

Height 68 mm

Wrench size, union nut 27 mm

External cable diameter 10 mm ... 16 mm

[Back to top](#)[Ambient conditions](#)

Degree of protection (IP) IP66

Ambient temperature (operation) -40 °C ... 125 °C

[Back to top](#)[General](#)

Size COM

Housing type Box mounting bases

Color black

Locking type with single locking latch

No. of cable outlets 1

Cable outlet lateral

Screw connection with

Type of the screw connection 1x M25

Housing material PA

Seal material NBR

Material lock PA

Flammability rating according to UL 94 V0

[Back to top](#)[Standards and Regulations](#)

Flammability rating according to UL 94 V0

[Back to top](#)[Environmental Product Compliance](#)

REACH SVHC Lead 7439-92-1

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 4.0 27140816

eCl@ss 4.1 27140816

eCl@ss 5.0 27143424

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)[ETIM](#)

ETIM 4.0 EC000437

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

Back to topUNSPSC

UNSPSC 6.01 31261502

UNSPSC 7.0901 31261502

UNSPSC 11 31261502

UNSPSC 12.01 31261502

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-SHOWS-1SGM25-PL-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.