

INDUSTRIAL COMPONENT DATA

HC-EVO-B24-SHWD-2SSM25-PLRBK 1421461 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-EVO-B24-SHWD-2SSM25-PLRBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-EVO-B24-SHWD-2SSM25-PLRBK
Catalog number	1421461
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-FF2800AE67
Generated	2026-08-05

Product Overview

Housing

Socket housing B24, with transverse flange, material: PA, cable outputs: 2, side, height: 84 mm, gland: sin, tubing: no, 2x M25, Standard, including 2x reduction adapters

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1421461

Packing unit 1 pc

Catalog page Page 626 (C-2-2017)

GTIN 4055626265049

Weight per Piece (excluding packing) 241.600 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 84 mm

Width 57 mm

Length 144 mm

Ambient conditions

Degree of protection of housing (IP) IP66

Degree of protection of housing (NEMA) 12 (UL 50e)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B24, BB46, D64, DD108, M, K, HV10-I-PT, HV 10-E...C

Size B24

Housing type Box mounting bases

Color black

Locking type with double locking latch

No. of cable outlets 2

Cable outlet lateral

Screw connection none

Type of the screw connection 2x M25

Housing material PA

Seal material NBR

Material lock PA

Flammability rating according to UL 94 V0

Assembly instructions Two plastic reductions M40 to M25 are provided

Connection One of the two openings for the screw connections is sealed but can be broken open using a screwdriver.

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 13.231261501

ETIM for 1421461 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

57 mm

Height (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-EVO-B24-SHWD-2SSM25-PLRBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.