

INDUSTRIAL COMPONENT DATA

HC-K10/26-EBUC 1580535 PHOENIX CONTACT media contacts, with contacts set of females connection, number of po..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-K10/26-EBUC



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-K10/26-EBUC
Catalog number	1580535
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-C842B064A6
Generated	2026-08-06

Product Overview

media contacts, with contacts set of females connection, number of poles 10 (250 V) / 16 (400 V) / 10 (1000 V), for housing HEAVYCON of the construction B16 and B32 (contacts, set CK1,6-ED... order separately)

Contact insert, number of poles: 10+16+10+2PE, size: B16, power contacts: 10, control contacts: 26, number of connections per pole: 1, Female, Crimped connection, 250 V, 10 A, 0.14 mm² ... 2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Holder female crimp contacts, number of contacts 10 (250 V) / 16 (400 V) / 10 (1000 V), for HEAVYCON housings of B16 and B32 execution (crimp contacts CK1,6-ED... must be ordered separately)

Commercial data

Order code One million five hundred eighty thousand five hundred thirty five

Packaging unit 10 stk

GTIN Four trillion forty six billion three hundred fifty six million four hundred sixty three thousand three hundred seventeen

Weight/PCs (without packing) 73,350 GRM

General information

Indication For housings HEAVYCON-ADVANCE and HEAVYCON type B16, crimp contacts CK 1,6-ED... (not included in delivery)

Connection method Crimped

The number of connection points per pole One

Pollution degree Three

Overvoltage category III

Poles 10+16+10+2PE

The number of power contacts Ten

The number of contacts the control circuit Twenty six

Cycles installation ≥ 500

Size B16

The wire cross section 0,14 mm² ... 2.5 mm²

Cross-section AWG 26 ... 14

The length of the stripped part of the wires 8 mm

6 mm (2.5 mm²)

Installation instructions Intended use provides integration into the housing with degree of protection IP54 or higher

Housing designs B16, plug-in connections are serviced only after disconnecting the load and the power supply.

Ambient conditions

Ambient temperature (operating) -40 °C ... 125 °C (including heating up of contacts)

Ambient temperature (when mounting) -40 °C ... 125 °C

Data on material

Material, contact Copper alloy

Material contact surface silver (or gold)

The material h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-K10/26-EBUC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.