

INDUSTRIAL COMPONENT DATA

HC-K12/2-ESTC-WS 1497713 PHOENIX CONTACT Contact insert, number of poles: 12+2+PE, size: B16, power contacts..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-K12/2-ESTC-WS



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-K12/2-ESTC-WS
Catalog number	1497713
Category	Contact insert for rectangular connectors
Minimum order	700 Pcs
Document ID	EO-3A0538075A
Generated	2026-08-06

Product Overview

Contact insert, number of poles: 12+2+PE, size: B16, power contacts: 12, control contacts: 2, Male, Crimp connection, 690 V, 40 A, 1.5 mm² ... 6 mm², Application: Power/Signal, without fixing screws M3 x 10 H1L

Contact insert, number of poles: 12+2+PE, size: B16, power contacts: 12, control contacts: 2, Male, crimped connection, 690 V, 40 A, 1.5 mm² ... 6 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral For HEAVYCON-ADVANCE and HEAVYCON housings of B16/B32 construction, power contacts: CK 4.0-ED, control contacts: CK 1.6-ED (crimped contacts not included in the scope of delivery)

General The connectors should be operated only without load/voltage.

assemblyInstallation instructions Proper use requires mounting in a housing with IP54 or higher degree of protection

Connection type Crimp connection

Item PropertiesConstruction B16

B32

Product Type Fixed pole contact insert

Number of poles 14

Plug Face 12+2+PE

Number of Power Contacts 12

Number of control contacts 2

Type of contact material Machining

Series HC-K

Insulation Properties

Surge Category Iii

Degree of pollution 3

DimensionsDimension Scheme

Width 34 mm

Height 39.6 mm

Longitude 84.5 mm

Horizontal Hole Spacing 77.5 mm

Mechanical Parameters

Contact Diameter 4 mm

Connection dataConnection technology

Connection technology Crimp Connection (Power Contacts)

Crimp Connection (Control Contacts)

Connecting Conductors

Connection Section 1.5 mm² ... 6 mm² (Power Contacts)

0.14 mm² ... 2.5 mm² (Control contacts)

AWG Connection Section 16 ... 10 (Power Contacts)

26 ... 14 (Command Contacts)

Tightening torque 0.8 Nm ... 1.2 Nm (PE connection)

0.5 Nm ... 0.8 Nm (HEAVYCON housing-mounting fixing screws)

Length to be de-isolated from the individual conductor 9 mm (Capacity 1.5 mm²|... 2.5 mm²)

8 mm (Control contacts, with a cross-section of 0.14 mm² ... 1.5 mm²)

9.5 mm (power contacts, with a cross-section of 4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-K12/2-ESTC-WS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.