

INDUSTRIAL COMPONENT DATA

HC-M-01-COAX-CK2,5-50-F 1066959 PHOENIX CONTACT

Connector HC-M-01-COAX-CK2,5-50-F 1066959

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-01-COAX-CK2,5-50-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-01-COAX-CK2,5-50-F
Catalog number	1066959
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-B7ED825A24
Generated	2026-08-06

Product Overview

Connector - HC-M-01-COAX-CK2,5-50-F - 1066959

Connector, number of poles: 1, power contacts: 0, control contacts: 1, Female, Crimped connection, 48 V, 16 A, 0.5 mm² ... 4 mm², cable outer diameter: 3 mm ... 9.5 mm, application: COAX, 50 ?

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Connector, power contacts: 0, control contacts: 1, Socket, 50 V, 16 A, 0.5 mm² ... 4 mm², external cable diameter: 3 mm ... 9.5 mm, 50 Ohm

Key Commercial Data

Orderkey 1066959

Packing unit 1

GTIN 4055626735122

Custom tariff number 85366990

General

Note Order crimp contacts separately

The potential of the EMC connector housing is isolated from the potential of the heavy connector.

Clamps for the clamping range of 3 mm - 6 mm and 6 mm - 9.5 mm

Can be used in Order No.: 1417376 HC-M-02-EMC-F

For 50 ? coaxial cables

Degree of pollution 3

Overvoltage category III

No. of power contacts 0

No. of control contacts 1

Insertion/withdrawal cycles ≥ 500

Conductor cross section 0.5 mm² ... 4 mm²

Connection cross section AWG 20 ... 12

Stripping length of the individual wire 8 mm (6 mm (for 2.5 mm²))

Minimum external conductor diameter 3 mm

Maximum external conductor diameter 9.5 mm

Assembly instructions Disassemble the connector from the plastic module using the tool, order no.: 1678635

HC-M-EMV-KON-EWZ

The round contact carrier can be separated in the middle for the purpose of mounting/removing the contact.

Connection Sheath stripping length: 23 mm, shield length: 13 mm, inner conductor stripping length: 8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Material data

Contact material Copper alloy

Contact surface material AU

Contact carrier material PC

Electrical characteristics

Rated voltage (III/3) 50 V

Rated surge voltage 0.8 kV

Rated current 16 A

Standards and Reg...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-01-COAX-CK2,5-50-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.