

INDUSTRIAL COMPONENT DATA

HC-M-02-CT-F 1414361 PHOENIX CONTACT Contact insert module

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-02-CT-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-02-CT-F
Catalog number	1414361
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-6B6916ADBFB
Generated	2026-08-06

Product Overview

Contact insert module

Contact insert module, number of poles: 2, power contacts: 2, control contacts: 0, Female, Crimped connection, 830 V, 40 A, 1.5 mm² ... 10 mm², Application: Power

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1414361

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 565 (C-2-2017)

GTIN 4055626025049

Weight per Piece (excluding packing) 11.310 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 42.4 mm

Width 34.2 mm

Length 14.6 mm

Electrical characteristics

Rated voltage (III/3) 1000 V

Rated current 40 A

Rated surge voltage 8 kV

Connection profile 2

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical characteristicsConductor cross section 1.5 mm² ... 10 mm²

Connection cross section AWG 16 ... 8

Stripping length of the individual wire 9 mm (for 1.5 ... 2.5 mm²)9.6 mm (for 4 mm² ... 6 mm²)18 mm (for 10 mm²)

Contact diameter 4 mm

Insertion/withdrawal cycles >= 500

General

Note For HEAVYCON housing type B6 to B48, HC-M-B...MF... hinged module carrier frame required, CK4,0..... crimp contacts, crimp contacts not supplied as standard.

Series HC-M-02

Color light gray

Number of module slots 1

Connection method Crimp connection

Connection in acc. with standard IEC / EN

Contact type turned

Flammability rating according to UL 94 V0

Degree of pollution 3

Overvoltage category III

Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required

Material data

Contact material Copper alloy

Contact surface material Ag

Contact carrier material PC

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-02-CT-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.