

INDUSTRIAL COMPONENT DATA

HC-M-02-PN-M-F 1417434 PHOENIX CONTACT Contact insert module

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-02-PN-M-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-02-PN-M-F
Catalog number	1417434
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-36109CE178
Generated	2026-08-05

Product Overview

Contact insert module

Contact insert module, number of poles: 2, Female, Male, application: Pneumatic system, for 6 mm hose inner diameter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1417434

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 583 (C-2-2017)

GTIN 4055626112954

Weight per Piece (excluding packing) 5.700 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 27.2 mm

Width 34.2 mm

Length 14.6 mm

Electrical characteristics

Connection profile 2

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Mechanical characteristics

Contact diameter 8 mm

Internal diameter of pressure hose connection 6 mm

Insertion/withdrawal cycles >= 500

General

Note For HEAVYCON ADVANCE housing type B6 to B24 and HEAVYCON housing type B6 to B48. HEAVYCON HC-M-B...-MF... module carrier frame required, HC-M-PN... pneumatic pins and sockets are not supplied as standard.

Series HC-M-02-PN

Integrated valve No

Color light gray

Number of module slots 1

Flammability rating according to UL 94 V0

Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required

Use of HC-CST-MOD (1636127) coding pins and HC-CBU-MOD (1636130) coding sockets has been prescribed.

Connection - Snap the pneumatic contact and module together. Insert the contact into the module from the front

- Place the modules assembled with the contacts in the module carrier frame.

- The pneumatic tubes are pushed onto the pneumatic contact from the back of the module.

The medium-sized module slots and sleeves/coupling housing with straight cable outlet direction are recommended.

Material da...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-02-PN-M-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.