

INDUSTRIAL COMPONENT DATA

HC-M-03/04-CT-M 1414364 PHOENIX CONTACT Contact insert module

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-03/04-CT-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-03/04-CT-M
Catalog number	1414364
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-0FFB413650
Generated	2026-08-06

Product Overview

Contact insert module

Contact insert module, number of poles: 3+4, power contacts: 3, control contacts: 4, Male, Crimped connection, 500 V, 40 A, 1.5 mm² ... 6 mm², application: Power/signal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1414364

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 565 (C-2-2017)

GTIN 4055626025070

Weight per Piece (excluding packing) 12.750 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 44.3 mm

Width 34.2 mm

Length 14.6 mm

Electrical characteristics

Rated voltage (III/3) 830 V (power contacts)

830 V (control contacts)

Rated current 40 A (power contacts)

10 A (control contacts)

Rated surge voltage 8 kV (power contacts)

8 kV (control contacts)

Connection profile 3+4

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical characteristicsConductor cross section 1.5 mm² ... 6 mm² (power contacts)0.14 mm² ... 2.5 mm² (control contacts)

Connection cross section AWG 16 ... 10 (power contacts)

26 ... 14 (control contacts)

Stripping length of the individual wire 9 mm (9.6 mm (4-6 mm²))8 mm (6 mm (2,5 mm²))

Contact diameter 4 mm

Wire diameter including insulation 5 mm (for power contacts)

Insertion/withdrawal cycles >= 500

Minimum housing height 52 mm

General

Note For HEAVYCON HC-B6 to B48 housing, HC-M-MHR... hinged retaining frame required, crimp connection, power contacts: CK 4,0-ED..., control contacts: CK 1,6-ED... (crimp contacts not supplied as standard)

Series HC-M-03/04

Color light gray

Number of module slots 1

Connection method Crimp connection (power contacts)

Crimp connection (control contacts)

Contact type turned

Flammability rating according to UL 94 V0

Degree of pollution 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-03/04-CT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.