


INDUSTRIAL COMPONENT DATA

HC-M-B10-MFH-B 1182088 PHOENIX CONTACT Module Support Framework - HC-M-B10-MFH-B

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-B10-MFH-B



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-B10-MFH-B
Catalog number	1182088
Category	Module carrier frame for industrial connectors
Minimum order	1 Pcs
Document ID	EO-EBCCCA291E
Generated	2026-07-31

Product Overview

Module Support Framework - HC-M-B10-MFH-B

Frame for module support, size: B10, type : for recessed side (a, b, c, ...), 4 mm² ... 6 mm², application: Module support frame

Frame for module support, size: B10, type: for recessed side (a, b, c, ...), 4 mm² ... 6 mm², Application: Frame for Module Support

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral This product replaces 1417399 HC-M-B10-MF-B

Item PropertiesProduct Type Frame for module support

Series HC-M-B

HC-M-02

HC-M-03

HC-M-03/04

HC-M-04

HC-M-05

HC-M-06

HC-M-08

HC-M-08-GBIT

HC-M-12

HC-M-17

HC-M-20

HC-M-25

HC-M-DSUB

HC-M-EMV

HC-M-HV

HC-M-HS

HC-M-00

application Frame for module support

Construction B10

Number of module seats 3

Execution for recessed side (a, b, c, ...)

Edge Type Frame for module support

Data Maintenance Status

Article Review 03

Connection dataConnecting Conductors

Connection Section 4 mm² ... 6 mm² (for PE conductor - power side)1 mm² ... 2.5 mm² (for PE driver - control side)

AWG Connection Section 12 ... 10 (for PE driver-power side)

18 ... 14 (for PE driver - control side)

Tightening torque 0.5 Nm ... 0.8 Nm (HEAVYCON housing-mounting fixing screws)

DimensionsDimension Scheme

Width 34.9 mm

Height 36 mm

Longitude 64 mm

Material DataContact Support Material Zinc die-cast alloy

Mechanical PropertiesMechanical data

Plug Cycles >= 500

Environmental and life-life conditionsEnvironmental conditions

Ambient Temperature (Service) -40 °C ... 125 °C

assemblyInstallation instructions HC-MHR-PE16 (1636981) to extend the PE connection to 16 mm².

For PE conductors, a conductor guard (PE connection screws without wire protection) must be used, in tubeless housings with side outlet the max. thread length of the bolt is 12 mm

When the module support frame is used in metal housings, the connection of the protective earth conductor must be....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-B10-MFH-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.