


INDUSTRIAL COMPONENT DATA

HC-M-B16-MFH-B 1182090 PHOENIX CONTACT Module Support Framework HC-M-B16-MFH-B

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-B16-MFH-B



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-B16-MFH-B
Catalog number	1182090
Category	Module carrier frame for industrial connectors
Minimum order	1 Pcs
Document ID	EO-B49A9C4944
Generated	2026-08-02

Product Overview

Module Support Framework - HC-M-B16-MFH-B

Frame for module support, size: B16, type : for recessed side (a, b, c, ...), 4 mm² ... 6 mm², application: Module support frame

Module frames, dimensions: B16, design: per flush-mounted side (a, b, c, ...), 4 mm² ... 6 mm², application: Module frames

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral notes This product replaces item 1417400 HC-M-B16-MF-B

Article featuresProduct Type Module frames

Series HC-M-B

HC-M-02

HC-M-03

HC-M-03/04

HC-M-04

HC-M-05

HC-M-06

HC-M-08

HC-M-08-GBIT

HC-M-12

HC-M-17

HC-M-20

HC-M-25

HC-M-DSUB

HC-M-EMV

HC-M-HV

HC-M-HS

HC-M-00

Application Module frames

type B16

B32

Number of module connection points 4

Execution for flush-mounted side (A, B, C, ...)

Frame type Module frames

Data maintenance status

Article review 03

Connection dataConductor connection

Connection section 4 mm² ... 6 mm² (for PE conductor - power side)1 mm² ... 2.5 mm² (For PE conductor - controller side)

AWG Connection Section 12 ... 10 (for PE conductor - power side)

18 ... 14 (For PE conductor - controller side)

Tightening torque 0.5 Nm ... 0.8 Nm (Fixing screws for mounting in the HEAVYCON enclosure)

dimensionsDimensioned Drawing

width 34.9 mm

height 36 mm

length 84.5 mm

Material informationContact Insert Material Zinc Die Cast Alloy

Mechanical characteristicsMechanical data

Manoeuvring cycles >= 500

Environmental and electrical life conditionsEnvironmental conditions

Ambient temperature (operating) -40 °C ... 125 °C

MontageMounting Note HC-MHR-PE16 (1636981) for PE connection extension to 16 mm².

Use suitable end protectors (PE connection screws without wire protection) with PE wires, max. thread length of the screw connection 12 mm in cases without pins with side exit

When inserting the module frame into metal enclosures, the connection of the PE....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-B16-MFH-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.