

INDUSTRIAL COMPONENT DATA

HC-M-B24-MF-B 1417402 PHOENIX CONTACT Module carrier frame

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-B24-MF-B



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-B24-MF-B
Catalog number	1417402
Category	Module carrier frame for industrial connectors
Minimum order	1 Pcs
Document ID	EO-4DB369C88E
Generated	2026-07-29

Product Overview

Module carrier frame

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1417402

Packing unit 1 pc

Catalog page Page 584 (C-2-2017)

GTIN 4055626112770

Weight per Piece (excluding packing) 71.580 g

Custom tariff number 85389099

Country of origin CN (China)

Dimensions

Height 36.5 mm

Width 34.4 mm

Length 111 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical characteristics

Conductor cross section 4 mm² ... 6 mm² (for PE conductor - power side)

1 mm² ... 2.5 mm² (for PE conductor - control side)

Connection cross section AWG 12 ... 10 (for PE conductor - power side)

18 ... 14 (for PE conductor - control side)

Insertion/withdrawal cycles ≥ 500

General

Type for the panel mounting side (a, b, c, ...)

Size B24

B48

Series HC-M-B

Color silver

Number of module slots 6

Assembly instructions HC-MHR-PE16 (1636981) for PE connection extension to 16 mm².

Connection Use wire end protection for PE wires (PE connection screws without wire protection) for housings without lateral connectors, max. thread length of the screw connection 12 mm

Material data

Contact carrier material Die-cast zinc alloy

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127143400eCl@ss 6.027261200eCl@ss 7.027440206eCl@ss 8.027440206eCl@ss 9.027440206

ETIM 5.0EC002312ETIM 6.0EC002312

UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-B24-MF-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.