

INDUSTRIAL COMPONENT DATA

HC-M-D15-MF-HB 1062122 PHOENIX CONTACT Module carrier frame

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-D15-MF-HB



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-D15-MF-HB
Catalog number	1062122
Category	Module carrier frame for industrial connectors
Minimum order	1 Pcs
Document ID	EO-2E493A9F2A
Generated	2026-08-02

Product Overview

Module carrier frame

Frame for module support, size: D15, 0.14 mm² ... 2.5 mm², application: Frame for module support, for housings size D15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1062122

Packing unit 1 pc

GTIN 4055626718040

Weight per Piece (excluding packing) 43.000 g

Custom tariff number 85389099

Country of origin CN (China)

Dimensions

Height 36 mm

Width 23 mm

Length 56.4 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical characteristics

Conductor cross section 0.14 mm² ... 2.5 mm² (applies to stranded conductors with ferrules)

Connection cross section AWG 24 ... 14

General

Note for modular contact inserts with a width of 14.6 mm in conjunction with size D15 housings.

Size D15

Assembly instructions Maximum allowable conductor cross section for the modules used: 2.5 mm²

Material data

Contact surface material Nickel

Contact carrier material Die-cast zinc alloy

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 6.027261200eCl@ss 7.027440206eCl@ss 9.027440206

ETIM 6.0EC002312

ETIM for 1062122 Connectors (EC002312)

Feature Name

Feature Value

With protective conductor (EF007468)

Yes

Min. number of insertion cycles (EF012212)

500

Inflammability class of insulation material according to UL94 (EF002521)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-D15-MF-HB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.