

INDUSTRIAL COMPONENT DATA

HC-M-DSUB 09-CT-M 1417309 PHOENIX CONTACT Contact insert module

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-DSUB 09-CT-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-DSUB 09-CT-M
Catalog number	1417309
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-21280167B5
Generated	2026-08-04

Product Overview

Contact insert module

Contact insert module, number of poles: 9, type: D-SUB9, Male, Crimped connection, 48 V, 1 A, 0.08 mm² ... 0.5 mm², application: Data, without crimped contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1417309

Packing unit 1 pc

Catalog page Page 575 (C-2-2017)

GTIN 4055626112510

Weight per Piece (excluding packing) 35.200 g

Custom tariff number 85389099

Country of origin CN (China)

Dimensions

Height 35.2 mm

Width 34.2 mm

Length 14.6 mm

Electrical characteristics

Rated voltage (III/3) 50 V

Rated current 1 A

Rated surge voltage 0.8 kV

Connection profile 9

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical characteristics

Conductor cross section 0.08 mm² ... 0.5 mm²

Connection cross section AWG 28 ... 20

Stripping length of the individual wire 4.2 mm

Contact diameter 1 mm

Insertion/withdrawal cycles ≥ 500

Minimum housing height 52 mm

General

Note

Type D-SUB 9

Series HC-M-DSUB-C

Color light gray

Number of module slots 1

Connection method Crimp connection

Contact type turned

Flammability rating according to UL 94 V0

Degree of pollution 3

Overvoltage category III

Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required

Use of HC-CST-MOD (1636127) coding pins and HC-CBU-MOD (1636130) coding sockets has been prescribed.

Connection Pin 8 = B

Pin 3 = A

Material data

Contact material Copper alloy

Contact surface material Ag

Contact carrier material PC

Phase conductor material Zinc alloy

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substanc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-DSUB 09-CT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.