

INDUSTRIAL COMPONENT DATA

HC-Q-I-RJ45I-AD-08-PC-M 1077119 PHOENIX CONTACT

Contact insert, number of positions: RJ45, size: D7, type : ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-Q-I-RJ45I-AD-08-PC-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-Q-I-RJ45I-AD-08-PC-M
Catalog number	1077119
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-DA6751889C
Generated	2026-08-06

Product Overview

Contact insert, number of positions: RJ45, size: D7, type : RJ45, Pin, 50 V, 1 A, application: Data, with adapter for RJ industrial connector

Contact insert, number of poles: RJ45, size: D7, type: RJ45, Male, 50 V, 1 A, application: Data, Adapter for RJ45 connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Technical dataNotesGeneral Refer to the accessories list for the corresponding RJ45 connectors

General Connectors may be operated only when there is no load/voltage.

Product propertiesProduct type Contact insert with a fixed no. of positions

Series HC-Q

Application Data

Type D7

Sensor type Ethernet

Number of positions 8

Connection profile RJ45

Type RJ45

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

DimensionsWidth 21 mm

Height 35 mm

Length 21 mm

Connection dataConnection technology

Connection in acc. with standard IEC / EN

Conductor connection

Tightening torque 0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)

Electrical propertiesRated voltage (III/3) 50 V

Rated surge voltage 0.8 kV

Rated current 1 A

Transmission characteristics (category) CAT5e

Mechanical propertiesMechanical data

Insertion/withdrawal cycles ≥ 500

Material specificationsFlammability rating according to UL 94 V0

Contact material Copper alloy

Contact surface material Au

Contact carrier material PC

Standards/regulations PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Standards and regulationsTesting

Standards/regulations PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-Q-I-RJ45I-AD-08-PC-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.