

## INDUSTRIAL COMPONENT DATA

# HC-STA-B06-HLFS-BLANK-EL-AL 1419900 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B06-HLFS-BLANK-EL-AL



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | PHOENIX CONTACT                    |
| MPN / Reference | HC-STA-B06-HLFS-BLANK-EL-AL        |
| Catalog number  | 1419900                            |
| Category        | Housing for rectangular connectors |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-EF3A321272                      |
| Generated       | 2026-08-04                         |

## Product Overview

### Housing

B6 overhead housing, for longitudinal flange, material: Die-cast aluminium, seawater resistant, variable, height: 52 mm, cable gland: without, Standard, without threaded hole for a screw

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                            |
|--------------|------------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |
|--------------|------------------------------------------------------------|

## Additional Product Information

### Key Commercial Data

Orderkey 1419900

Packing unit 1 pc

Catalog page Page 647 (C-2-2017)

GTIN 4055626201245

Weight per Piece (excluding packing) 122.000 g

Custom tariff number 85389099

Country of origin CN (China)

### Dimensions

Height 52 mm

Width 44 mm

Length 60 mm

Ambient conditions

Degree of protection of housing (IP) IP66

IP67

Degree of protection of housing (NEMA) 4 (UL 50e)

4X (UL 50e)

12 (UL 50e)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B6, BB10, DD24, M

Size B6

Housing type Sleeve housing

Color gray aluminum

Locking type for single locking latch

Cable outlet Variable

Screw connection none

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 13.231261501

ETIM for 1419900 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

44 mm

Height (EF000040)

52 mm

Depth (EF000049)

60 mm

Type of housing (EF006980)

Plug case

Housing material (EF001596)

Aluminium

Coating housing (EF001601)

Uncoated

Housing colour (EF000136)

Other

Position cable feed (EF008218)

Other

Position of the shackle (EF008459)

Other

With cable screw gland (EF000735)

No

Mounting method of the ca...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B06-HLFS-BLANK-EL-AL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.