

INDUSTRIAL COMPONENT DATA

HC-STA-B24-HHFD-2TTM32-EL-AL 1079581 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B24-HHFD-2TTM32-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-B24-HHFD-2TTM32-EL-AL
Catalog number	1079581
Category	Housing for rectangular connectors
Minimum order	50 Pcs
Document ID	EO-77D6B1EDDE
Generated	2026-08-02

Product Overview

Housing

B24 aerial housing, for cross flange, material: Injected cast aluminum, seawater resistant, cable outlets: 2, straight, 2x M32, height: 76 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1079581
Packing unit 1 pc
Minimum order quantity 50 pc
GTIN 4055626801056
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85389099
Country of origin PL (Poland)
Dimensions
Classifications
General
Dimensions
Height 76 mm

Width 44 mm

Length 120 mm

[Back to top](#)General

Locking type for double locking latch

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

[Back to top](#)Classifications

eCl@ss

eCl@ss 10.0.1 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

[Back to top](#)ETIM

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

[Back to top](#)

ETIM for 1079581 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

44 mm

Height (EF000040)

76 mm

Depth (EF000049)

120 mm

Type of housing (EF006980)

Plug case

Housing material (EF001596)

Aluminium

Coating housing (EF001601)

Uncoated

Housing colour (EF000136)

Other

Position cable feed (EF008218)

Other

Position of the shackle (EF008459)

None

With cable screw gland (EF000735)

No

Mounting method of the cable gland (EF012210)

Metric

With hinged lid (EF000117)

No

With distance piece (EF005072)

No

With sealing (EF005610)

No

Number of conduit inlets (EF000437)

2

Type of locking (EF000208)

Double locking levers

Operating temperature (EF002393)

-40 °C

EMC-version (EF001062)

Yes

Degree of protection (IP), mounted (EF007466)

IP66

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B24-HHFD-2TTM32-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.