

INDUSTRIAL COMPONENT DATA

HC-STA-B24-HLFD-2SM25-EL-AL 1423609 PHOENIX CONTACT Housing HC-STA-B24-HLFD-2SM25-EL-AL 1423609

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B24-HLFD-2SM25-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-B24-HLFD-2SM25-EL-AL
Catalog number	1423609
Category	Housing for rectangular connectors
Minimum order	50 Pcs
Document ID	EO-56DD4BB9A7
Generated	2026-08-05

Product Overview

Housing - HC-STA-B24-HLFD-2SM25-EL-AL - 1423609

B24 aerial housing, for cross flange, material: Injected cast aluminum, seawater resistant, cable outlets: 2, side, 2x M25, height: 60 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Sleeve housing B24, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 2, lateral, height: 60 mm, cable gland: none, support sleeve: no, 2x M25, Standard

Key Commercial Data

Orderkey 1423609

Packing unit 1

GTIN 4055626349701

Custom tariff number 85389099

Dimensions

Height 60 mm

Width 44 mm

Length 120 mm

Ambient conditions

Degree of protection of housing (IP) IP66

IP67

Degree of protection of housing (NEMA) 4 (UL 50e)

4X (UL 50e)

12 (UL 50e)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M

Size B24

Housing type Sleeve housing

Locking type for double locking latch

No. of cable outlets 2

Cable outlet lateral

Screw connection none

Type of the screw connection 2x M25

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

Classifications

eCI@ss

eCI@ss 5.1 27261200

eCI@ss 6.0 27261200

eCI@ss 7.0 27440202

eCI@ss 8.0 27440202

eCI@ss 9.0 27440202

ETIM

ETIM 6.0 EC000437

ETIM 7.0 EC000437

ETIM for 1423609 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

44 mm

Height (EF000040)

60 mm

Depth (EF000049)

120 mm

Type of housing (EF006980)

Plug case

Housing material (EF001596)

Aluminium

Coating housing (EF001601)

Uncoated

Position cable feed (EF008218)

Sideways

Position of the shackle (EF008459)

None

With cable screw gland (EF000735)

No

Mounting method of the cable gland (EF012210)

Metric

With hinged lid (EF000117)

No

With distance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B24-HLFD-2SM25-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.