

INDUSTRIAL COMPONENT DATA

HC-STA-D15-HHFS-1STM25-ELC-AL 1424346 PHOENIX CONTACT Sleeve housing D15, for single locking latch, material..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-D15-HHFS-1STM25-ELC-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-D15-HHFS-1STM25-ELC-AL
Catalog number	1424346
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-99F423233A
Generated	2026-08-04

Product Overview

Sleeve housing D15, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, height: 68 mm, cable gland: none, support sleeve: no, 1x M25, Standard

D15 aerial housing, for longitudinal flange, material: Die-cast aluminum, seawater resistant, cable outlets: 1, side, 1x M25, height: 68 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Sleeve housing D15, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, height: 68 mm, cable gland: none, support sleeve: no, 1x M25, Standard

Key Commercial Data

Orderkey 1424346

Packing unit 1 pc

Catalog page Page 519 (C-2-2017)

GTIN 4055626370828

Weight per Piece (excluding packing) 127.300 g

Custom tariff number 85389099

Country of origin CN (China)

Ambient conditions

Degree of protection (IP) IP66

IP67

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-D15, A10

Size D15

Housing type Sleeve housing

Color gray aluminum

Locking type for single locking latch

No. of cable outlets 1

Cable outlet lateral

Screw connection none

Type of the screw connection 1x M25

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

Seal material NBR, conductive

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

eCl@ss

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440202

eCl@ss 8.0 27440202

eCl@ss 9.0 27440202

ETIM

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

ETIM for 1424346 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

30 mm

Height (EF000040)

68 mm

Depth (EF000049)

63.5 mm

Type of housing (EF006980)

Plug case

Housing material (EF001596)

Aluminium

Coating housing (EF001601)

Uncoated

Housing colour (EF00013...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-D15-HHFS-1STM25-ELC-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.