

INDUSTRIAL COMPONENT DATA

HC-STA-D15-SLWSC-2SSP16-EL-AL 1424372 PHOENIX CONTACT Box mounting bases D15, with single locking latch, mat..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-D15-SLWSC-2SSP16-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-D15-SLWSC-2SSP16-EL-AL
Catalog number	1424372
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-EC43E3258F
Generated	2026-08-05

Product Overview

Box mounting bases D15, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 2, lateral, height: 52 mm, cable gland: none, support sleeve: no, 2x Pg16, protective cover: yes, Standard

D15 socket housing, with longitudinal flange, material: Injected cast aluminum, seawater resistant, protective cap material: PC, cable outlets: 2, side, 2x Pg16, height: 52 mm, cable gland: without, protective cover: yes, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Box mounting bases D15, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 2, lateral, height: 52 mm, cable gland: none, support sleeve: no, 2x Pg16, protective cover: yes, Standard

Key Commercial Data

Orderkey 1424372

Packing unit 1 pc

Catalog page Page 521 (C-2-2017)

GTIN 4055626371122

Weight per Piece (excluding packing) 170.000 g

Custom tariff number 85389099

Country of origin CN (China)

Ambient conditions

Degree of protection (IP) IP66 (with locked protective cover)

IP67 (when plugged in)

Ambient temperature (operation) -40 °C ... 125 °C

General

Size D15

Housing type Box mounting bases

Color gray aluminum

Locking type with single locking latch

No. of cable outlets 2

Cable outlet lateral

Screw connection none

Type of the screw connection 2x Pg16

Protective cover yes

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

Material lock PA

Material, protective cover PA

Assembly instructions One opening is sealed with a plastic filler plug and can be opened using a screwdriver.

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

eCI@ss

eCI@ss 5.1 27261200

eCI@ss 6.0 27261200

eCI@ss 7.0 27440202

eCI@ss 8.0 27440202

eCI@ss 9.0 27440202

ETIM

ETIM 5.0 EC000437

ETIM 6.0 EC000437

ETIM 7.0 EC000437

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-D15-SLWSC-2SSP16-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.