

INDUSTRIAL COMPONENT DATA

HC-STA-D25-HCLWS-PL-BK 1424400 PHOENIX CONTACT

Protective covers

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-D25-HCLWS-PL-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-D25-HCLWS-PL-BK
Catalog number	1424400
Category	Cap for industrial connectors
Minimum order	1 Pcs
Document ID	EO-1B0537B9A2
Generated	2026-08-03

Product Overview

Protective covers

D25 protective cap, with longitudinal flange, protective cap material: PA, height: 19 mm

Protective cover D25, with single locking latch, protective cover material: PA, height: 19 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type Protective cover

Housing type Protective cover

Type D25

Data management status

Article revision 03

DimensionsDimensional drawing

Width 33 mm

Height 19 mm

Length 80 mm

Material specificationsMaterial Protective cover PA

Flammability rating according to UL 94 V0

Material, protective cover PA

Environmental and real-life conditionsAmbient conditions

Degree of protection IP66

Ambient temperature (operation) -20 °C ... 100 °C

Mounting Assembly note Plastic protective cover for short-term protection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-D25-HCLWS-PL-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.