

INDUSTRIAL COMPONENT DATA

HCC 4-CLT-NS35 SET 1279180 PHOENIX CONTACT Surge Protection Base Element, For CLIXTRAB Surge Protection, Sui..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCC 4-CLT-NS35 SET



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCC 4-CLT-NS35 SET
Catalog number	1279180
Category	Installation clamp for meters
Minimum order	50 Pcs
Document ID	EO-12BB1A76C7
Generated	2026-08-04

Product Overview

Surge Protection Base Element, For CLIXTRAB Surge Protection, Suitable for HCC 4 Series, Nominal Voltage: 400 V, Mounting Class: NS 35/7.5, NS 35/15, Color: Grey

CLIXTRAB surge protection base element, for surge protection suitable for the HCC 4 series, rated voltage: 400 V, mounting type: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral notes for surge protection CLIXTRAB suitable for the HCC 4 series

General notes

note The use of surge protection plugs reduces the load current of the terminal block (see technical data for CLT surge protection plugs).

Article featuresProduct Type Feed-through clamp

No. of poles 10

Number of connections 10

Insulation characteristics

Overvoltage Category Iii

Degree of pollution 2

Electrical characteristicsSizing Impulse Voltage 4 kV
Connection dataNumber of connections per plan 10
Standard-compliant connection IEC 61984
Nominal voltage 400 V
dimensionswidth 72.6 mm
height 75.9 mm
Depth 35.3 mm
Material informationColor grey
Combustibility class according to UL 94 V0
Insulation Material Group The
Insulation material PA
Cold static insulation material insert -60 °C
Insulation Material Relative Temperature Index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface Flammability NFPA 130 (ASTM E 162) Exceeded
NFPA 130 (ASTM E 662) Specific Optical Density of Fumes Exceeded
NFPA 130 Fume Toxicity (SMP 800C) Exceeded
Environmental and electrical life conditionsBroadband vibration/noise
Test Specification DIN EN 50155 (VDE 0115-200):2018-05
Spectrum Electrical Life Check Category 1, Class B, Body Mounted
Frequency...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCC 4-CLT-NS35 SET with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.