

**INDUSTRIAL COMPONENT DATA**

# HCS-C MAXI 1W C C C 7035 2203166 PHOENIX CONTACT

## Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MAXI 1W C C C 7035



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | HCS-C MAXI 1W C C C 7035 |
| Catalog number  | 2203166                  |
| Category        | Electronic enclosure     |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-F3BFB28564            |
| Generated       | 2026-08-04               |

### Product Overview

Electronic housing

C-Maxi portable case in light gray, consisting of two halves with screws, 1.1 mm front with window reinforcement and keyboard slot

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

### Additional Product Information

Key Commercial Data

Orderkey 2203166

Packing unit 1 pc

GTIN 4055626377766

Weight per Piece (excluding packing) 214.100 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-C MAXI 1W C C C 7035

Order No. 2203166

Housing type Handheld housing

Type straight

Battery compartment no

**Measurements****Dimensional drawing**

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [ w ] 94 mm

Height [ h ] 182.5 mm

Depth [ d ] 39 mm

Diagonal 2.8 in. (Window for display)

Dimensions 73 mm x 80 mm x 1.1 mm (Recessed area on front)

73 mm x 7.9 mm x 1.1 mm (Recessed area on front)

73 mm x 8 mm x 1.1 mm (Recessed area on front)

62 mm x 33 mm (Window for display)

**Material specifications**

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

**Hammer test**

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

**Packaging information**

Pieces per package 1

Denomination packing units Pcs.

**Standards and regulations**

Flammability rating according to UL 94 V0

**Classifications**

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC001031

ETIM for 2203166 Ca...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MAXI 1W C C C 7035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.