

INDUSTRIAL COMPONENT DATA

HCS-C MAXI 1W C C C 7035 2203166 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MAXI 1W C C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MAXI 1W C C C 7035
Catalog number	2203166
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-F3BFB28564
Generated	2026-08-05

Product Overview

Electronic housing

C-Maxi portable case in light gray, consisting of two halves with screws, 1.1 mm front with window reinforcement and keyboard slot

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203166

Packing unit 1 pc

GTIN 4055626377766

Weight per Piece (excluding packing) 214.100 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-C MAXI 1W C C C 7035

Order No. 2203166

Housing type Handheld housing

Type straight

Battery compartment no

Measurements**Dimensional drawing**

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [w] 94 mm

Height [h] 182.5 mm

Depth [d] 39 mm

Diagonal 2.8 in. (Window for display)

Dimensions 73 mm x 80 mm x 1.1 mm (Recessed area on front)

73 mm x 7.9 mm x 1.1 mm (Recessed area on front)

73 mm x 8 mm x 1.1 mm (Recessed area on front)

62 mm x 33 mm (Window for display)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Packaging information

Pieces per package 1

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC001031

ETIM for 2203166 Ca...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MAXI 1W C C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.