

INDUSTRIAL COMPONENT DATA

HCS-C MINI C 3AAA 1 1 7035 2203151 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI C 3AAA 1 1 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MINI C 3AAA 1 1 7035
Catalog number	2203151
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-0700829BBB
Generated	2026-08-03

Product Overview

Electronic housing

C-Mini portable case in light gray, smooth closed front made up of two halves, two screens on the front side, screws, battery compartment cover and battery contacts for 3 AAA batteries

Light grey C-Mini portable case, flat front, consisting of two half-shells, two front covers, screws, battery compartment cover and battery contacts for 3 AAA batteries

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203151

Packing unit 1 pc

GTIN 4055626377049

Weight per Piece (excluding packing) 110.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-C MINI C 3AAA 1 1 7035

Order No. 2203151

Housing type Handheld housing

Type straight

Battery compartment 3 x AAA

Measurements

Dimensional drawing

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [w] 70.5 mm

Height [h] 110 mm

Depth [d] 26 mm

Front with faceplate top, 1 x (49.8 mm x 17.8 mm)

bottom, 1 x (49.8 mm x 17.8 mm)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Packaging information

Pieces per package 1

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss
7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 13.239121409

ETIM for 2203151 Cabinets a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI C 3AAA 1 1 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.