

INDUSTRIAL COMPONENT DATA

HCS-T MEDIUM 1W C C 1 7035 2203139 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-T MEDIUM 1W C C 1 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-T MEDIUM 1W C C 1 7035
Catalog number	2203139
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-882AC6AEB6
Generated	2026-08-05

Product Overview

Electronic housing

T-Medium portable case in light gray, made up of two halves, screen on the lower front side with screws, 1.1 mm front with reinforcement, with window and keyboard slot

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2203139

Packing unit 1 pc

GTIN 4055626376929

Weight per Piece (excluding packing) 229.900 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-T MEDIUM 1W C C 1 7035

Order No. 2203139

Housing type Handheld housing

Type stepped

Battery compartment no

Measurements**Dimensional drawing**

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [w] 92 mm

Height [h] 216 mm

Depth [d] 40 mm

Diagonal 2.8 in. (Window for display)

Dimensions 64 mm x 116.7 mm x 1.1 mm (Recessed area on front)

71 mm x 10 mm x 1.1 mm (Recessed area on front)

63 mm x 40 mm (Window for display)

38 mm x 3.3 mm (Opening for membrane cable)

Front with faceplate bottom, 1 x (59.9 mm x 17.9 mm)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Packaging information

Pieces per package 1

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-T MEDIUM 1W C C 1 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.