

INDUSTRIAL COMPONENT DATA

HCS-T MICRO X 2AA C C 7035 2203127 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-T MICRO X 2AA C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-T MICRO X 2AA C C 7035
Catalog number	2203127
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-EB591231B4
Generated	2026-08-05

Product Overview

Electronic housing

T-Micro portable housing in light grey, consisting of two halves, screws, front with 1.1 mm reinforcement, closed with keyboard slot, cover for battery compartment and battery contacts, for 2 AA batteries

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203127

Packing unit 1 pc

GTIN 4055626376851

Weight per Piece (excluding packing) 105.500 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-T MICRO X 2AA C C 7035

Order No. 2203127

Housing type Handheld housing

Type straight

Max. IP code to attain IP40

Battery compartment 2 x AA

Measurements

Dimensional drawing

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [w] 48 mm

Height [h] 150 mm

Depth [d] 28 mm

Dimensions 38 mm x 140 mm x 1.1 mm (Recessed area on front)

Material specifications

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Degrees of protection provided by enclosures (IP code)

Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08

Result, degree of protection, IP code IP40

Packaging information

Pieces per package 1

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-T MICRO X 2AA C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.