

## INDUSTRIAL COMPONENT DATA

# HDFK 95-F-VP GNYE 0717665 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFK 95-F-VP GNYE



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | HDFK 95-F-VP GNYE                 |
| Catalog number  | 0717665                           |
| Category        | Panel feed-through terminal block |
| Minimum order   | 10 Pcs                            |
| Document ID     | EO-B3E47C9A2A                     |
| Generated       | 2026-08-06                        |

## Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Terminal connection, number of poles: 1, charging current: 232 A, cross-section: 35 mm<sup>2</sup> - 95 mm<sup>2</sup>, conductor connection direction with respect to the plug direction: 0 °, width: 25 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0717665

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4017918976798

Weight per Piece (excluding packing) 176.300 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2

Nominal cross section 95 mm<sup>2</sup>

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Nominal current I<sub>N</sub> 232 A

Maximum load current 232 A

Nominal voltage U<sub>N</sub> 630 V (metal panels 2.5 mm ... 5 mm)

Number of positions 1

Dimensions

Width 25 mm

Length 91.5 mm

Pitch 25 mm

Plate thickness 1 mm ... 6 mm

Connection data

Note Terminal sleeve

Connection side outside

Connection method Screw connection

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 35 mm<sup>2</sup>

Conductor cross section solid max. 95 mm<sup>2</sup>

Conductor cross section flexible min. 35 mm<sup>2</sup>

Conductor cross section flexible max. 95 mm<sup>2</sup>

Conductor cross section AWG min. 4

Conductor cross section AWG max. 3/0

Conductor cross section flexible, with ferrule without plastic sleeve min. 30 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 95 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 30 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sle...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFK 95-F-VP GNYE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.