

INDUSTRIAL COMPONENT DATA

HDFK 95-VP 0717979 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFK 95-VP



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFK 95-VP
Catalog number	0717979
Category	Panel feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-278F0A3936
Generated	2026-08-05

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Terminal connection, number of poles: 1, charging current: 232 A, cross-section: 35 mm² - 95 mm², conductor connection direction with respect to the plug direction: 0 °, width: 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 0717979

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4046356286121

Weight per Piece (excluding packing) 174.480 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2

Nominal cross section 95 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum load current 232 A

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 232 A

Maximum load current 232 A

Nominal voltage U_N 1000 V (With metal panels of 1 mm ... 2.5 mm)

800 V (With metal panels over 2.5 mm ... 5 mm)

690 V (With metal panels over 5 mm ... 6 mm)

Open side panel No

Number of positions 1

Dimensions

Width 25 mm

Pitch 25 mm

Plate thickness 1 mm ... 6 mm

Connection data

Note Terminal sleeve

Connection side outside

Connection method Screw connection

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 35 mm²

Conductor cross section solid max. 95 mm²

Conductor cross section flexible min. 35 mm²

Conductor cross section flexible max. 95 mm²

Conductor cross section AWG min. 4

Conductor cross section AWG max. 2/0

Conductor cross section flexible, with ferrule without plastic sleeve min. 25 mm²

Conductor cross section flexible, with ferrule withou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFK 95-VP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.