

INDUSTRIAL COMPONENT DATA

PTSM 0,5/ 2-HHI0-2,5-SMD WHR24 1815196 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSM 0,5/ 2-HHI0-2,5-SMD WHR24



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSM 0,5/ 2-HHI0-2,5-SMD WHR24
Catalog number	1815196
Category	Printed circuit board connector
Minimum order	500 Pcs
Document ID	EO-FF2BC18E02
Generated	2026-08-03

Product Overview

Feed-through header

Printed circuit board base case, nominal section: 0.5 mm², color: white signals, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: PTSM 0.5/.. -HHI-SMD WH, pitch: 2.5 mm, mounting: SMD soldering, pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, plug-in system: COMBICON PTSM, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: 24 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1815196

Packing unit 500 pc

Minimum order quantity 500 pc

Catalog page Page 399 (C-1-2013)

GTIN 4046356761406

Weight per Piece (excluding packing) 1.410 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 14 mm

Width 9.8 mm

Pitch 2.5 mm

Dimension a 2.5 mm

Width [w] 9.8 mm

Height [h] 5 mm

Height 5 mm

Length 14 mm

General

Range of articles PTSM 0,5/...HHI-SMD WH

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Nominal current I_N 6 A

Maximum load current 6 A

Insulating material PA

Flammability rating according to UL 94 V0

Color white

Number of positions 2

Standards and Regulations

Connection in acc. with standard UL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121409

ETIM for 1815196 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSM 0,5/ 2-HHI0-2,5-SMD WHR24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.