


INDUSTRIAL COMPONENT DATA

MCV 0,5/16-G-2,54 P20 THR R72 1821533 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 0,5/16-G-2,54 P20 THR R72



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 0,5/16-G-2,54 P20 THR R72
Catalog number	1821533
Category	Printed circuit board connector
Minimum order	315 Pcs
Document ID	EO-F669961FE7
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 0.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 16, number of rows: 1, number of poles: 16, number of connections: 16, family of articles: MCV 0.5/.. -G-THR, pitch: 2.54 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON FMC 0.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 72 mm wide strap, Sample quantities available under SAMPLE MC...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1821533

Packing unit 315 pc

Minimum order quantity 315 pc

Note Made to Order (non-returnable)

Catalog page Page 177 (C-1-2013)

GTIN 4046356789691

Weight per Piece (excluding packing) 4.120 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 4.85 mm

Width 45.22 mm

Pitch 2.54 mm

Dimension a 38.1 mm

Width [w] 45.22 mm

Height [h] 9.1 mm

Height 7.1 mm

Length of the solder pin 2 mm

Pin dimensions 0.64 x 0.64 mm

Length 4.85 mm

General

Range of articles MCV 0,5/...-G-THR

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 32 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 160 V

Connection in acc. with standard EN-VDE

Nominal current I_N 6 A

Insulating material LCP

Flammability rating according to UL 94 V0

Color black

Number of positions 16

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 0,5/16-G-2,54 P20 THR R72 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.