


INDUSTRIAL COMPONENT DATA

MCV 0,5/ 7-G-2,54 P20THRR44C1 1706181 PHOENIX CONTACT Header, Nominal current: 6 A, Rated voltage (III/2): 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 0,5/ 7-G-2,54 P20THRR44C1



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 0,5/ 7-G-2,54 P20THRR44C1
Catalog number	1706181
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-C6C238AC88
Generated	2026-08-04

Product Overview

MCV 0,5/ 7-G-2,54 P20THRR44C1 1706181 PHOENIX CONTACT Header, Nominal current: 6 A, Rated voltage (III/2): 1..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Type of accessory/spare part	Charger
Mains voltage	100 V - 240 V AC
Suitable for	CF-CRIMPHANDY
Output voltage	12 V DC
Charging current	2 A

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Header, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 7, Pitch: 2.54 mm, Color: black, Contact surface: Gold, Mounting: Taped SMD/THT/THR components, Fixed coding of the first position, can be combined with the FMC 0,5/...-ST-2,54 C1 connector

Printed circuit board base housing, nominal section: 0.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: MCV 0.5/.. -G-THR, pitch: 2.54 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON FMC 0.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 44 mm wide strap, Fixed first pole coding, can be combined with FMC 0.5/...-ST-2.54 C1 connector

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 0,5/ 7-G-2,54 P20THRR44C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.