


## INDUSTRIAL COMPONENT DATA

# MC 1,5/ 2-GF-3,5 P20 THRR32 1789397 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 2-GF-3,5 P20 THRR32



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MC 1,5/ 2-GF-3,5 P20 THRR32     |
| Catalog number  | 1789397                         |
| Category        | Printed circuit board connector |
| Minimum order   | 400 Pcs                         |
| Document ID     | EO-4000F66987                   |
| Generated       | 2026-08-03                      |

## Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MC 1.5/.. -GF-THR, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: Screw lock, fixing type: Air clamping (thread), packaging type: 32 mm wide strap  
PCB headers, nominal cross section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Pin, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: MC 1,5/..-GF-THR, pitch: 3.5 mm, mounting: THR soldering / wave soldering, pin layout: Linear pinning, solder pin [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, Pin connector pattern alignment: Standard, locking: Screw locking mechanism, mounting: Threaded flange, type of packaging: 32 mm wide tape

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family MC 1,5/..-GF-THR

Product line COMBICON Connectors S

Type Component suitable for through hole reflow

Number of positions 2  
Pitch 3.5 mm  
Number of connections 2  
Number of rows 1  
Number of potentials 2  
Mounting flange Threaded flange  
Pin layout Linear pinning  
Solder pins per potential 1  
Data management status  
Article revision 04  
Electrical propertiesNominal current IN 8 A  
Nominal voltage UN 160 V  
Contact resistance 1.3 m?  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 160 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 250 V  
Rated surge voltage (II/2) 2.5 kV  
MountingMounting type THR soldering / wave soldering  
Pin layout Linear pinning  
Flange  
Tightening torque 0.3 Nm  
Processing notes  
Process Reflow/wave soldering  
Moisture Sensitive Level MSL 1  
Classification temperature Tc 260 °C  
Solder cycles in the reflow 3  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface contact area (top layer) Tin (3 - 5 µm Sn)  
Metal surface contact area (middle layer) Nickel (1 - 3 µm Ni)  
Metal surface soldering area (top layer) Tin (3 - 5 µm Sn)  
Metal surface soldering area (middle layer) Nickel (1 - 3 µm Ni)  
Material data - housing  
Color (Housing) black (9005)  
Insulating material LCP  
Insulating material group IIIa  
CTI according t...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 2-GF-3,5 P20 THRR32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.