


INDUSTRIAL COMPONENT DATA

DFK-IPC 16/ 2-GF-SH-10,16 1702976 PHOENIX CONTACT
Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-IPC 16/ 2-GF-SH-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-IPC 16/ 2-GF-SH-10,16
Catalog number	1702976
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-A8152FFCED
Generated	2026-08-02

Product Overview

DFK-IPC 16/ 2-GF-SH-10,16 1702976 PHOENIX CONTACT Feed-through header

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Bus
Number of poles (EF001391)	2
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	10.16 mm
Modular spacing connections (EF006827)	10.16 mm
Rated current I _n (EF008250)	76 A
Rated voltage (EF000228)	1000 V
Rated surge voltage (EF002993)	8 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Material of contact surface (EF004020)	Silver
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	1.7 mm
Length pin (EF006825)	4.1 mm

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Material insulation body (EF007543)	Other
Housing colour (EF000136)	Green
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of fastening (EF002442)	Other
Type of banding (EF007011)	Carton (for SMD)

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Feed-through header

Wall pass-through housing, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: DFK-IPC 16/.. -GF-SH, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4.1 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-IPC 16/ 2-GF-SH-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.