

INDUSTRIAL COMPONENT DATA

DFK-MSTBVA 2,5/ 6-GF-5,08 1899320 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-MSTBVA 2,5/ 6-GF-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-MSTBVA 2,5/ 6-GF-5,08
Catalog number	1899320
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-3A99F0287A
Generated	2026-07-28

Product Overview

Printed-circuit board connector

Through-wall housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: DFK-MSTBVA 2.5/.. -GF, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1899320

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 355 (C-1-2013)

GTIN 4017918186340

Weight per Piece (excluding packing) 6.900 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 12 mm

Pitch 5.08 mm

Dimension a 25.4 mm

Height 19 mm

Length of the solder pin 3.9 mm

Length 12 mm

General

Range of articles DFK-MSTBVA 2,5/..-GF

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Maximum load current 12 A

Insulating material PBT

Flammability rating according to UL 94 V0

Color green

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss
7.027141134eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001283ETIM 4.0EC001283ETIM 5.0EC002637ETIM 6.0EC001283

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121410

ETIM for 1899320 Connectors (EC002637)

Feature Name

Feature Value....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-MSTBVA 2,5/ 6-GF-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.