


**INDUSTRIAL COMPONENT DATA**

# DFK-PC 5/ 5-GFU-SH-7,62 1716205 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 5/ 5-GFU-SH-7,62



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | DFK-PC 5/ 5-GFU-SH-7,62         |
| Catalog number  | 1716205                         |
| Category        | Printed circuit board connector |
| Minimum order   | 10 Pcs                          |
| Document ID     | EO-D05D333A76                   |
| Generated       | 2026-07-31                      |

### Product Overview

Printed-circuit board connector

Feed-through housing, nominal section: 6 mm<sup>2</sup>, color: green, nominal current: 41 A, dimensioning voltage (III/2): 630 V, contact surface: Tin, contact type: Male, Number of potentials: 5, Number of rows: 1, Number of poles per row: 5, number of connections: 5, family of articles: DFK-PC 5/.. -GFU-SH, pitch: 7.62 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 4.26 mm, Stecksystem: POWER COMBICON 5, Locking: Screw lock, packaging type: boxed

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 1716205

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 547 (C-1-2013)

GTIN 4046356136822

Weight per Piece (excluding packing) 26.760 g

Custom tariff number 85366990

Country of origin PL (Poland)

**Dimensions**

Length [ l ] 29.25 mm

Width 72.72 mm

Pitch 7.62 mm

Dimension a 30.48 mm

Width [ w ] 72.72 mm

Height [ h ] 21.1 mm

Height 19.54 mm

Length of the solder pin 4.26 mm

Pin spacing 7.62 mm

Length 29.25 mm

**General**

Range of articles DFK-PC 5/...-GFU-SH

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 800 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 41 A

Maximum load current 41 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 5

**Standards and Regulations**

Connection in acc. with standard EN-VDE

**CUL**

Flammability rating according to UL 94 V0

**Environmental Product Compliance**

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss  
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPS...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 5/ 5-GFU-SH-7,62 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.