

**INDUSTRIAL COMPONENT DATA**

# DFK-PC 6-16/ 4-G-10,16 1701472 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 6-16/ 4-G-10,16



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | DFK-PC 6-16/ 4-G-10,16          |
| Catalog number  | 1701472                         |
| Category        | Printed circuit board connector |
| Minimum order   | 10 Pcs                          |
| Document ID     | EO-720828F253                   |
| Generated       | 2026-07-29                      |

## Product Overview

Feed-through header

Wall pass-through housing, nominal section: 16 mm<sup>2</sup>, color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: DFK-PC 6-16/.. -G, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4.1 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 1701472

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 574 (C-1-2013)

GTIN 4046356030540

Weight per Piece (excluding packing) 26.500 g

Custom tariff number 85366990

Country of origin PL (Poland)

**Dimensions**

Length [ l ] 46.4 mm

Width 60.08 mm

Pitch 10.16 mm

Dimension a 30.48 mm

Width [ w ] 60.08 mm

Height [ h ] 23.1 mm

Height 19 mm

Length of the solder pin 4.1 mm

Pin dimensions 1.2 x 1 mm

Pin spacing 10.16 mm

Length 46.4 mm

**General**

Range of articles DFK-PC 6-16/..-G

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 76 A

Maximum load current 76 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 4

**Standards and Regulations**

Connection in acc. with standard EN-VDE

**CUL**

Flammability rating according to UL 94 V0

**Environmental Product Compliance**

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UN...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 6-16/ 4-G-10,16 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.